



バリオリング


VWBG-V



VWBG



■吊り方と荷重方向



型名	基本使用荷重			自重 [kg]	T [mm]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G [mm]	M	トルク [Nm]
	X [t]	Y [t]	Z [t]											
VWBG-V バリオリング メートル並目														
VWBG-V 0.3t-M8	0.3	0.4	0.6	0.18	76	8	31	29	30	28	13	36	M8	10
VWBG-V 0.45t-M10	0.45	0.6	0.9	0.29	78	8	31	29	33.5	30	17	38	M10	10
VWBG-V 0.6t-M12	0.6	0.75	1.2	0.41	107	10	49	35	42	36	21	47	M12	10
VWBG-V 1.0t-M14 (F=21)	1	1.25	2	0.63	114	13	46	38	48	41	21	56	M14	25
VWBG-V 1.3t-M16	1.3	1.5	2.6	0.69	114	13	46	38	48	41	25	56	M16	30
VWBG-V 1.8t-M18 (F=27)	1.8	2	3.6	1.18	137	13	54	35	62	55	27	67	M18	50
VWBG-V 2.0t-M20	2	2.5	4	1.42	137	13	54	35	62	55	33	67	M20	70
VWBG-V 2.0t-M22 (F=33)	2	2.5	4	1.45	137	13	54	35	62	55	33	67	M22	100
VWBG-V 3.5t-M24	3.5	4	7	2.63	173	18	66	40	81	70	40	88	M24	150
VWBG-V 3.5t-M27 (F=41)	3.5	4	7	2.65	173	18	66	40	81	70	41	88	M27	200
VWBG-V 5.0t-M30	5	6	10	5.09	221	22	90	50	99	85	50	106	M30	225
VWBG バリオリング メートル並目														
VWBG 6(7.5)t-M33 (F=50)	6	7.5	15	4.69	208	22	86	50	90	80	50	96	M33	350
VWBG 8(10)t-M36	8	10	15	4.72	208	22	86	50	90	80	54	94	M36	410
VWBG 12(13)t-M42	12	13	17	6.10	234	26	111	65	98	85	63	95	M42	550
VWBG 12(15)t-M45	12	15	18	6.24	234	26	111	65	98	85	67	95	M45	550
VWBG 13(16)t-M48	13	16	18	6.37	234	26	111	65	98	85	68	95	M48	550
VWBG 14(20)t-M52	14	20	25	10.55	271	32	119	70	120	95	78	120	M52	750
VWBG 16(22)t-M56	16	22	28	10.68	271	32	119	70	120	95	84	120	M56	800
VWBG 16(22)t-M60 (F=90)	16	22	28	11.37	271	32	119	70	120	95	90	120	M60	800
VWBG 16(25)t-M64	16	25	28	11.40	271	32	119	70	120	95	94	120	M64	800
VWBG 31.5(40)t-M72	31.5	40	50	29.96	338	46	130	90	170	145	108	159	M72	1200
VWBG 35(48)t-M80	35	48	50	31.19	338	46	130	90	170	145	120	159	M80	1500
VWBG 40(50)t-M90	40	50	50	34.39	378	46	168	110	170	145	135	159	M90	2000
VWBG 40(50)t M100 (F=150)	40	50	50	36.50	378	46	168	110	170	145	150	159	M100	2000

◎上記以上のサイズも～M150まで対応可能。詳しくはお問合せ下さい。

▲相手面に密着させて使用して下さい。